SAFETY DATA SHEET



1. Identification

Product identifier SYLVALITE™ RE 100S

Other means of identification

SDS number 8843

200000000391 **Product Code**

Recommended use Industrial uses: Uses of substances as such or in preparations at industrial sites. Formulation

[mixing] of preparations and/or re-packaging (excluding alloys).

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information Company Kraton Chemical, LLC **Address** P.O. Box 550850 Jacksonville, FL

32255-0850 Zip

USA Country

904-928-8700 **Phone Number Alternate Phone Number** 800-526-5294 904-928-8780 **Fax Number**

CHEMTREC 800-424-9300 **Emergency-US**

2. Hazard(s) identification

Physical hazards Not classified. **Health hazards** Not classified. **OSHA** defined hazards Combustible dust

Label elements

Hazard symbol None. Signal word Warning

Hazard statement May form combustible dust concentrations in air.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Prevent dust accumulation to minimize

explosion hazard. Observe good industrial hygiene practices.

Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to Response

extinguish.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%
Resin acids and Rosin acids, esters with pentaerythritol		8050-26-8	99-100

Material name: SYLVALITE™ RE 100S SDS US

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contactWash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

Dusts may irritate the respiratory tract, skin and eyes.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Apply extinguishing media

carefully to avoid creating airborne dust.

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

High concentration of airborne dust may form explosive mixture with air. Static charges generated by emptying package in or near flammable vapor may cause flash fire. During fire, gases hazardous to health may be formed. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Wear suitable protective equipment. Move containers from fire area if you can do so without risk.

tions containers from fire area if you can do so without risk.

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards May form combustible dust concentrations in air.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Use only non-sparking tools. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Never return spills to original containers for re-use.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Minimize dust generation and accumulation. Avoid significant deposits of material, especially on horizontal surfaces, which may become airborne and form combustible dust clouds and may contribute to secondary explosions. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Explosion-proof general and local exhaust ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Follow all SDS/label precautions even after container is emptied because they may retain product residues.

Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Store at ambient temperature and atmospheric pressure.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-3 (29 CFR 1910.1000)

Additional components Value **Form** Type Dust **TWA** 5 ma/m3 Respirable fraction. Total dust. 15 mg/m3

No biological exposure limits noted for the ingredient(s). **Biological limit values**

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Eye wash fountain and emergency showers are recommended.

9. Physical and chemical properties

Pellets. **Appearance** Physical state Solid. **Form** Solid.

Light yellow. Color

Mild. Odor

Odor threshold Not available. Not available. Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

595.4 °F (313.0 °C) Cleveland Open Cup Flash point

0 (n-BuAc=1) estimated **Evaporation rate**

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

(%)

Not available.

Not available. **Explosive limit - lower (%)** Explosive limit - upper (%) Not available.

Vapor pressure < 0.001 mm Hg at 20°C

Vapor density Not available.

Relative density 1.08 OECD 105 at 25°C/25°C; (water=1)

Solubility(ies)

Solubility (water) insoluble

Material name: SYLVALITE™ RE 100S

Partition coefficient 3.6 at 20°C

(n-octanol/water)

Auto-ignition temperature 750.2 °F (399 °C)

Decomposition temperature Not available.

Viscosity Not available.

Other information

Chemical family Rosin Ester

Density 1080.00 kg/m3 at 20°C

Percent volatile 0 % estimated

Softening point 210.2 °F (99 °C) Ring & Ball

Weighted solids 100 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Strong oxidizing agents. Keep away from heat, sparks and open flame. Contact with incompatible

materials. Minimize dust generation and accumulation.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Upon decomposition this product emits acrid dense smoke with carbon dioxide, carbon monoxide,

water and other products of combustion.

11. Toxicological information

Information on likely routes of exposure

Inhalation Dust may irritate respiratory system.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Resin acids and Rosin acids, esters with pentaerythritol Irritation Corrosion - Eye, No eye irritation.

Result: Negative

Species: New Zealand white rabbit

Organ: Eye Test Duration: 72 hr Observation Period: 7 days Notes: OECD 405

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Dusts may irritate the respiratory tract, skin and eyes.

Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components Species Test Results

Resin acids and Rosin acids, esters with pentaerythritol (CAS 8050-26-8)

Acute Dermal

LD50 New Zealand white rabbit > 2000 mg/kg, 14 days At this dose no

death occurred.; OECD 402.

Rabbit > 2000 mg/kg, 24 Hours

Oral

LD50 Rat > 2000 mg/kg

Sprague-Dawley rat > 2000 mg/kg, 14 days At this dose no

death occurred.; OECD 425

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Material name: SYLVALITE™ RE 100S

SDS US

^{*} Estimates for product may be based on additional component data not shown.

Corrosivity

Resin acids and Rosin acids, esters with

pentaerythritol

Irritation Corrosion - Skin, No skin irritation.

Result: Negative

Species: New Zealand white rabbit

Organ: Skin Test Duration: 4 hr Observation Period: 72 hr Notes: OECD 404

Serious eve damage/eve

irritation

Direct contact with eyes may cause temporary irritation.

Eye Contact

Resin acids and Rosin acids, esters with

pentaerythritol

Irritation Corrosion - Eye, No eye irritation.

Result: Negative

Species: New Zealand white rabbit

Organ: Eve Test Duration: 72 hr

Observation Period: 7 days Notes: OECD 405

Respiratory or skin sensitization

Not available. Respiratory sensitization

Skin sensitization This product is not expected to cause skin sensitization.

Skin sensitization

Resin acids and Rosin acids, esters with

pentaerythritol

Local Lymph Node Assay - Lowest Concentration Producing

Reaction, Not a skin sensitizer.

Result: Negative Species: Mouse Organ: Skin Notes: OECD 429

Maximisation Assay (Magnusson and Kligman), Not a skin

sensitizer. Result: Negative Species: Guinea pig Organ: Skin Notes: OECD 406

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Mutagenicity

Resin acids and Rosin acids, esters with

pentaerythritol

Germ Cell Mutagenicity: Ames, No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Result: Negative

Species: Salmonella typhimurium

Notes: OECD 471

Germ Cell Mutagenicity: Chromosome Abberation, This material is considered to be non-clastogenic to human

lymphocytes in vitro. Result: Negative Species: Human Notes: OECD 473

In vitro gene mutation study in mammalian cells

Result: Negative Species: Mouse Notes: OECD 476

Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Not available. Specific target organ toxicity -

single exposure

Material name: SYLVALITE™ RE 100S 8843 Version #: 5.0 Revision date: 12-01-2020 Issue date: 10-21-2014 Specific target organ toxicity -

repeated exposure

Not available.

ropodica exposure

Aspiration hazard Not available.

Further information

Resin acids and Rosin acids, esters with pentaerythritol Cytotoxicity - in Vitro, Not cytotoxic

Result: Negative Species: Human Organ: Fibroblasts cells Notes: BS 30993-5

Cytotoxicity - in Vitro, Not cytotoxic

Result: Negative Species: Human Organ: Lung cell tissue Notes: BS 5736

Cytotoxicity - in Vitro, Not cytotoxic

Result: Negative Species: Mouse Organ: Fibroblasts cells Test Duration: 72 hr Observation Period: 24 hr

Notes: BS 5736

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Resin acids and Rosin a	acids, esters with p	entaerythritol (CAS 8050-26-8)	
Aquatic			
Algae	EL50	Green algae (Selenastrum capricornutum)	> 1000 mg/l, 72 hr OECD 201
	NOEL	Green algae (Selenastrum capricornutum)	1000 mg/l, 72 hr OECD 201
Crustacea	EL50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hr OECD 202
	NOEC	Water flea (Daphnia magna)	1000 mg/l, 48 hr OECD 202
Fish	LL50	Fathead minnow (Pimephales promelas)	> 1000 mg/l, 96 hr OECD 203
	NOEL	Fathead minnow (Pimephales promelas)	1000 mg/l, 96 hr OECD 203

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability Not readily degradable.

Biodegradability

Percent degradation (Aerobic biodegradation)

Resin acids and Rosin acids, esters with pentaerythritol 0 % OECD 301B

Result: Not readily biodegradable. Species: Activated sewage sludge

Test Duration: 28 days

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

SYLVALITE™ RE 100S 3.6, at 20°C

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

8843 Version #: 5.0 Revision date: 12-01-2020 Issue date: 10-21-2014

Material name: SYLVALITE™ RE 100S

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not available.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

All components are either listed on the US EPA TSCA Inventory list and

designated as "active" or are exempt from listing.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard

Combustible dust

categories

Acute toxicity (any route of exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

16. Other information, including date of preparation or last revision

Issue date 10-21-2014 12-01-2020 **Revision date**

Version #

Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the **Further information**

Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

NFPA ratings Health: 1

Flammability: 1 Instability: 0

Material name: SYLVALITE™ RE 100S

SDS US 8843 Version #: 5.0 Revision date: 12-01-2020 Issue date: 10-21-2014

NFPA ratings



Disclaimer

KRATON CORPORATION urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information set forth in this document, as of the date of this document, is based on present knowledge, obtained from reliable sources and made to our reasonable ability and in good faith. Such information is made without any warranty or guarantee whatsoever, and shall establish no legal duty or responsibility on the part of the author(s), their employer or its affiliates. The information given is designed only as guidance and its completeness is not guaranteed. The information is not a guarantee of any specific product properties, features, qualities or specifications.

The information relates only to the specific product designated as shipped, and may not be valid for such product used in combination with any other materials or products, or in any process, unless expressly specified in this document. Nothing set forth in this document shall be construed as a recommendation or license to use any product in conflict with, or as claimed by, any existing patents rights. The user alone must finally determine whether a contemplated use of a product will infringe any such patents. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities are in compliance with all Local, Federal and International Legislation and Local Permits.

We, for ourselves and on behalf of our affiliates, expressly disclaim any and all liability for any damages or injuries arising out of any activities relating in any way to the information set forth in this document. Due to the proliferation of sources for information, we are not and cannot be responsible for SDSs obtained from any other source other than ourselves. If you have obtained an SDS from another source or if you are not sure that the SDS you have is current, please contact us for the most current version.

*KRATON, the KRATON logo, the "Green Super Drop" logo, 1101, ABIETA, AQUATAC, CENTURY, CENWAX, ELEXAR, E-LEXAR, , IPD, NEXAR, SYLFAT, SYLVABLEND, SYLVACOTE, SYLVAFUEL, SYLVAGUM, SYLVALITE, SYLVAMIN, SYLVAPINE, SYLVAPRINT, SYLVARES, SYLVAROAD, SYLVAROS, SYLVASOL, SYLVATAC, SYLVATAL, SYLVATRAXX, UNICLEAR, UNIDYME, UNIFLEX, UNI-TAC, and ZONATAC are either trademarks or registered trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2016 Kraton Corporation

Revision information

This document has undergone significant changes and should be reviewed in its entirety.