# KRATON

K0442 North America 2/7/2023

# KRATON™ D1162 P Polymer

**Data Document** 

Identifier: K442DDI23U

## Description

Kraton D1162 P is a clear, linear triblock copolymer based on styrene and isoprene with a polystyrene content of 43%. It is supplied from North America in the physical form identified below.

- Kraton D1162 PT supplied as a dusted dense pellet with talc
   Kraton D1162 PK supplied as a dusted dense pellet with kaolin

Kraton D1162 P is used as an ingredient in formulating adhesives, sealants and coatings. It may also find use as a modifier of bitumen or thermoplastics and in compound formulations.

Kraton D1162 PT and Kraton D1162 PK are variations of the same polymer, produced on the same production assets.

Sales Specifications				
<u>Property</u>	Test Method	<u>Units</u>	Sales Specification Range	<u>Notes</u>
Antioxidant	KM 08	%m	0.08 TO 0.30	
Dust, Fine Talc	BAM 908	%w	0.15 TO 0.35	b
Dust, Kaolin	BAM 908	%w	0.10 TO 0.50	a
Polystyrene Content	KM 03	%m	40.0 TO 46.0	
Total Extractables	KM 05	%m	<= 1.0	
Vis, Sol (Toluene) 25.0%w @25C	BAM 922	сР	100 TO 140	
<b>a</b> Kaolin				
<b>b</b> Talc				

Typical Properties (These are typical values and may not routinely be measured on finished product)						
<u>Property</u>	Test Method	<u>Units</u>	<u>Typical Value</u>	<u>Notes</u>		
Specific Gravity	ASTM D 792		0.92			
Melt Index 200°C, 5 kg	ASTM D 1238	gms/10 min.	45			

### Packaging

Kraton's products are available in a number of different package types. For information specific to this grade, please contact your local Kraton representative.

#### **End Use Requirements**

The end user of the product is solely responsible to comply with all regulatory and testing requirements applicable to the end use of the finished article incorporating the product.

Information regarding the regulatory status of the product is available from Kraton on request.

#### **Safety and Handling Precautions**

Read the GHS Data Sheet carefully and thoroughly before handling and using the product. If you are unable to locate the GHS Safety Data Sheet from www.kraton.com, please contact the Product Safety support team at product.safety@kraton.com.

#### Legal Disclaimer

We cannot anticipate all circumstances, conditions or applications in which this information, our products, or the products of other suppliers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or for the safety or suitability of our products, either alone or in combination with other products. The user of our products bears the responsibility of determining their suitability for a particular application or formulation, or determining that the products or their use do not infringe any intellectual property. Unless otherwise stated in writing, WE MAKE NO WARRANTY REGARDING THE INFORMATION PROVIDED HEREIN OR OUR PRODUCT, EITHER EXPRESS OR IMPLIED, EXCEPT AS SET FORTH IN ANY APPLICABLE CONTRACT THAT MAY BE IN PLACE BETWEEN KRATON AND THE CUSTOMER OR, ABSENT SUCH A CONTRACT, KRATON'S TERMS AND CONDITIONS OF SALE. The end user assumes all responsibility and liability for loss or damage arising from the handling and use of Kraton's products, whether used alone or in combination with other products.

KRATON and the Kraton logo are either trademarks or registered trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2023 Kraton Corporation

#### For Further Information

U.S.A Headquarters
Kraton Corporation
15710 John F. Kennedy Blvd.
Suite 300
Houston, Texas 77032
+1-800-4-KRATON (800-457-2866)
info@kraton.com

# Asia Pacific Regional Headquarter/ Innovation Center Rm 2201, No.688, West Nan Jing Road Shanghai, 200041, PR China +86 21 2082 3888 info.cn@kraton.com

#### Europe, Middle East, Africa Kraton Polymers Nederland B.V. Transistorstraat 16 NL - 1322 CE Almere The Netherlands +31 36 546 2846 info@kraton.com