KRATON

K711 North America 9/30/2021

KRATON™ D1192 K Polymer

Data Document

Identifier : K711DDc21U

Description

Kraton D1192 K is a clear linear block copolymer based on styrene and butadiene with bound styrene of 30% mass. It is supplied from North America in the physical forms described below:

- Kraton D1192 KT supplied as porous pellets dusted with talc
 Kraton D1192 KTM supplied as powder dusted with talc for the North American market

Kraton D1192 K is used for modification of industrial and paving bitumen. It may also be suitable for use in formulating adhesives, sealants and coatings, and in the modification of polymers.

Sales Specifications							
Property	Test Method	<u>Units</u>	Sales Specification Range	Notes			
Polystyrene Content	KM 03	%m	30.5 TO 34.5				
Vinyl Content	KM 03	%	>= 35				
Total Extractables	KM 05	%m	<= 1.0				
Volatile Matter	KM 04	%m	<= 1.0				
Antioxidant	BAM 929	%w	0.20 TO 0.40	а			
Solution Viscosity	BAM 922	cP		b			
Dust (KT)	BAM 908	%w	0.15 TO 0.35	с			
Dust (KTM)	BAM 908	%w	4.00 TO 6.00	с			
a Non-staining phen	olic antioxidant						
b 25%w toluene solu	25%w toluene solution at 25 degrees C						
c Talc							

Typical Properties (These are typical values and may not routinely be measured on finished product)							
Prop	<u>perty</u>	Test Method	<u>Units</u>	Typical Value	Notes		
Tens	sile Strength	ASTM D 412	psi	4600	d		
300	% Modulus	ASTM D 412	psi	700	d		
Elon	ngation at Break	ASTM D 412	%	1000	d		
Spe	cific Gravity	ISO 2781		0.94			
Hard	dness, Shore A (15 sec)	ASTM D 2240	Hardness, Shore A (15 sec)	70	е		
Melt	Flow Rate, 200C/5kg	ISO 1133	g/10min.	Less Than 1			
Solu	tion Viscosity	BAM 922	cps	1800	f		
d	Measured on film cast from toluene solution.						
е	e Measured on slabs compression molded at 350F.						
	Management on 250/ management in talyons at 25 C						

Measured on 25% mass solution in toluene at 25 C f

Packaging

Kraton Polymers are available in a number of different package types. For information specific to this grade, please contact your local Kraton Polymers representative.

KRATON and the Kraton logo are either trademarks or registered trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2021 Kraton Corporation

End Use Requirements

If the finished article is intended for use in food contact and packaging applications, toys, or human contact areas, manufacturers of the final product should observe all relevant regulations. Some of these regulations require tests to be carried out on the final product, e.g. migration. These are the responsibility of the final product manufacturer. Information on the food packaging clearances of individual products is available from Kraton Polymers.

Safety and Handling Precautions

Read the GHS Data Sheet carefully and thoroughly before beginning any work.

Legal Disclaimer

We cannot anticipate all circumstances, conditions or applications in which this information, our products, or the products of other suppliers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or for the safety or suitability of our products, either alone or in combination with other products. The user of our products bears the responsibility of determining their suitability for a particular application or formulation, or determining that the products or their use do not infringe any intellectual property. Unless otherwise stated in writing, WE MAKE NO WARRANTY REGARDING THE INFORMATION PROVIDED HEREIN OR OUR PRODUCT, EITHER EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY. The buyer assumes all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.

For Further Information

U.S.A Headquarters Kraton Polymers U.S. LLC 15710 John F. Kennedy Blvd. Suite 300 Houston, Texas 77032 +1-800-4-KRATON (800-457-2866) info@kraton.com Asia Pacific Regional Headquarter/ Innovation Center Rm 2201, No.688, West Nan Jing Road 100 Century Avenue Shanghai, 200041, PR China +86 21 2082 3888 info.cn@kraton.com Europe, Middle East, Africa Kraton Polymers Nederland B.V. Transistorstraat 16 NL - 1322 CE Almere The Netherlands +31 36 546 2846 info@kraton.com